UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/743,866	12/24/2003	Eui-Sun Hong	1568.1082	9364
49455 STEIN MCEW	7590 06/02/200 EN. LLP	EXAMINER		
1400 EYE STREET, NW			ECHELMEYER, ALIX ELIZABETH	
	SUITE 300 WASHINGTON, DC 20005			PAPER NUMBER
			1795	
			MAIL DATE	DELIVERY MODE
			06/02/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)				
	10/743,866	HONG ET AL.				
Office Action Summary	Examiner	Art Unit				
	Alix Elizabeth Echelmeyer	1795				
The MAILING DATE of this communication app	ears on the cover sheet with the c	orrespondence address				
Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period v - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tim vill apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1)⊠ Responsive to communication(s) filed on 11 M	arch 2009.					
	action is non-final.					
· <u> </u>						
closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4)⊠ Claim(s) <u>1-10 and 13-15</u> is/are pending in the application.						
4a) Of the above claim(s) is/are withdrawn from consideration.						
5) Claim(s) is/are allowed.						
6)⊠ Claim(s) <u>1-10 and 13-15</u> is/are rejected.						
7) Claim(s) is/are objected to.						
8) Claim(s) are subject to restriction and/or	r election requirement.					
Application Papers						
9) The specification is objected to by the Examine	r.					
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).						
a) ☐ All b) ☐ Some * c) ☐ None of:						
1. Certified copies of the priority documents have been received.						
2. Certified copies of the priority documents have been received in Application No						
3. Copies of the certified copies of the priority documents have been received in this National Stage						
application from the International Bureau (PCT Rule 17.2(a)).						
* See the attached detailed Office action for a list of the certified copies not received.						
Attachment(s)						
1) Notice of References Cited (PTO-892)	4) Interview Summary					
2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08)	Paper No(s)/Mail Da 5) Notice of Informal P					
Paper No(s)/Mail Date	6) Other:					

Application/Control Number: 10/743,866 Page 2

Art Unit: 1795

DETAILED ACTION

Response

1. This Office Action is in response to the Remarks filed March 11, 2008. No claims are amended, added, or cancelled. Claims 1-10 and 13-15 are pending and are rejected for the reasons given below.

Translation of JP 04-184861

2. Applicant requested a "competent" English translation of the Japanese document used in the Non-Final Rejection of December 17, 2008. While the burden is on the Applicant to come forward with evidence that the examiner did not provide a *prima facie* case of obviousness (see MPEP 2141 IV, 2142), the examiner has obtained a certified translation of the document. In light of the translation, the rejection is withdrawn.

Claim Rejections - 35 USC § 103

3. Claims 1-7, 10, and 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morishita et al. (US 5,976,729) in view of Nakanishi et al. (US 2002/0142211).

Morishita et al. teach a battery cell having an outer can made from aluminum or aluminum alloy (abstract).

Morishita et al. teach that the cell has an outer can containing an electrode assembly and electrolyte, a sealing lid, and a bottom on which a layer of nickel is

Art Unit: 1795

provided on the outer surface of only the bottom portion of the can and not on the side wall of the can (Figure 6, column 4 lines 1-9).

The nickel layer of Morishita et al. is 0.10 mm, or 100 µm (column 5 lines 30-38). With regard to claim 4, the layer may also comprise copper (column 3 line 20).

Claims 3 and 5 are a process-by-product claim. The product produced by the process-by-product claims 3 and 5 are the product stated in claims 2 and 4, respectively. The cited references teach a product that is the same as, or an obvious variant of, the product set forth in claims 2 and 4, respectively. Claims 3 and 5 are alternatively unpatentable. The product of claims 2 and 3, and the product of claims 4 and 5, appear to be the same. See MPEP 2113 and In re Marosi, 710 F.2d 799, 218 USPQ 289 (Fed. Cir. 1983)

As for claim 6, the bottom surface of the battery can is welded to a first lead plate and the first lead plate is welded via resistance welding to a second lead plate for connection to the battery (column 1 lines 54-61; column 2 lines 59-63).

Claim 7 is a process-by-product claim. The product produced by the process-by-product claim 7 is the product stated in claim 6. The cited references teach a product that is the same as, or an obvious variant of, the product set forth in claim 7. Claim is alternatively unpatentable. The product of claim 6 and the product of claim 7 appear to be the same. See MPEP 2113 and In re Marosi, 710 F.2d 799, 218 USPQ 289 (Fed. Cir. 1983)

Art Unit: 1795

With regard to claim 10, Morishita et al. disclose a reliable protective circuit or safety device having leads connecting the battery and the associated protective circuit or safety device (column 1 lines 54-61; column 2 lines 59-63).

Morishita et al. fail to teach that the sealing lid is welded to the can.

Nakanishi et al. teach a secondary wound battery having an end cap attached to the can by welding ([0012], [0142]).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to attach the cap of Morishita et al. by welding such as taught by Nakanishi et al. since welding would ensure that the electrode assembly and electrolyte solution were sealed within the battery can, preventing leakage and allowing for electricity generation.

4. Claims 8 and 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morishita et al. in view of Nakanishi et al. as applied to claim 6 above, and further in view of Seiji (Japan 60 124351). Additionally, datasheets for copper and copper alloys have been cited as evidence as discussed below.

The teachings of Morishita et al. and Nakanishi et al. as discussed above are incorporated herein.

Morishita et al. in view of Nakanishi et al. do not teach an outside layer comprised of a first material and a lead connected thereto comprised of a second

Page 5

material having a melting point different from the layer material by 500 °C or 200°C or less. Morishita discloses that a two-layer lead is attached to the bottom surface of the battery.

The first layer of the lead is aluminum or an aluminum alloy and the second layer being nickel or a nickel-plated iron, nickel-plated stainless, or nickel-platted copper (col. 2 lines 33-36; col. 3 lines 18-20).

Morishita et al. in view of Nakanishi et al. do not explicitly teach that the melting point of the materials differ by 500°C or less or that they differ by 200°C or less.

Seiji teaches a nonaqueous electrolyte cell having a copper layer on the outside surface of the positive electrode enclosure or can (See abstract). Seiji teaches that the use of nickel or copper on the outside surface of the terminal face reduces the contact resistance.

A lead constructed of a copper-nickel alloy has a melting point of 1170 °C (Cupper & Alloys datasheet, page 3). The copper outside layer of the battery can has a melting point of 1083 (chemical Elements Basic Information-Copper). Therefore, the melting point of the battery can outside layer and the lead material differ by 200 °C or less.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the battery can outside layer of Morishita et al. in view of Nakanishi et al. to use copper in the construction of the battery can as taught by Seiji to reduce the contact resistance. The melting point of Copper differs by 500 °C, 200 °C, or less from the melting point of the lead construction material, a copper-nickel alloy taught

by Morishita et al. The proper selection of the construction materials in contact in the battery eliminates the adverse effects such as corrosion that result from joining dissimilar metals.

5. Claims 13 and 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Morishita et al. in view of Nakanishi et al. as applied to claim 1 above, and further in view of Shibata et al. (EP 0 899 799 A2).

The disclosures of Morishita et al. and Nakanishi et al. as discussed above are incorporated herein.

Morishita et al. in view of Nakanishi et al. do not teach a metal layer between the layer and the outer surface of the can having a first material selected from Zn, Sn, Fe, and Cr.

Shibata discloses a jar can for a secondary battery. The bottom surface of the battery can consist of multiple layers. Layer 1 is the aluminum or aluminum alloy of the battery can bottom surface. Layer 2 is the layer adjacent to the exterior to the bottom of the can and is constructed of iron or a ferrous alloy. Layer 3 is the layer adjacent to the exterior surface of the iron layer and it is constructed of nickel (paragraphs18-23). The iron layer maintains the stiffness or structural strength of the can and the use of aluminum reduces the weight of the battery can (paragraphs 19-21).

The reference does not explicitly state that the material in layer 1 is the same as the material in layer 3. The aluminum alloy of layer 1 may contain nickel as a common material.

Application/Control Number: 10/743,866 Page 7

Art Unit: 1795

It would have been obvious to one having ordinary skill in the art at the time of the invention to modify Morishita et al. in view of Nakanishi et al. to include iron as an internal layer of the bottom of the battery can to ensure the structural strength of the can is maintained as taught by Shibata et al.

Response to Arguments

6. Applicant's arguments, see Remarks, filed March 11, 2009, with respect to the rejection(s) of claim(s) 1 under JP 04-184861 have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made, see above.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Alix Elizabeth Echelmeyer whose telephone number is (571)272-1101. The examiner can normally be reached on Mon-Fri 8-5:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Patrick Ryan can be reached on 571-272-1292. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/743,866 Page 8

Art Unit: 1795

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/PATRICK RYAN/ Supervisory Patent Examiner, Art Unit 1795

Alix Elizabeth Echelmeyer Examiner Art Unit 1795

aee